



10.	Washer	0.3T Steel	1	Nickel Plated
9.	Nut	2.1T Brass	1	Nickel Plated
8.	Insulator B	Bakelite	1	Red Color
7.	Insulator A	Bakelite	1	Red Color
6.	Pin(2.5 ϕ)	Copper	1	Nickel Plated
5.	Bushing	Brass	1	Nickel Plated
4.	Housing	PBT	1	Black Color
3.	Break Terminal	0.3T Brass	1	Silver Plated
2.	Sleeve Spring	0.4T Phosphor Bronze	1	Silver Plated
1.	Pin Terminal	0.3T Brass	1	Silver Plated
NO.	Description	Material	Q'TY	Finish

SPECIFICATIONS:
 Contact Resistance : 30m Ω max
 Current Rating : Max 2.0A , 16V DC
 Insulation Resistance : 100M Ω min. at DC 500V
 Dielectric Withstand Voltage : AC 500V for one minute
 Remark: ▲ : The Most Important Dimension

SCHEMATIC		
	Part number	Pin Dia.(mm)
	SCD-026-PCB	ϕ 2.0
	SCD-026-A-PCB	ϕ 2.5

DATE	DWN	CHKD	APVD	MANAGER
01.11.2011				

PART NAME :DC POWER JACK PART NUMBER: SCD-026-PCB

TOLERANCE : \pm 0.3mm UNLESS OTHERWISE SPECIFIED

VERSION:6.0

UNIT:mm

SCALE:/