



**(COMPONENT SIDE)
PCB LAYOUT**

USB - B - HR - S - 1 2 3
Part Number

- | | |
|----------------------|--------------------|
| 1. Contact Plating | 2. Shell Plating |
| N: *Nickel Plating | N: Nickel plated |
| B: Gold Flash | G: Gold plated |
| C: 30u" Gold Plating | 3. Insulator Color |
| | *-: White |
| | B: Black |

NO.	NAME	MATERIAL	FINISH	REMARK	Q'TY
1	HOUSING	NYLON PA6T G.F	WHITE		1
2	PIN TERM.	PHOS. BRONZE T:0.25	GOLD/TIN PLATED	Gold flash and tin plating-optional (Gold pins are of lead free plating)	4
3	SHELL	BRASS T:0.3	NICKEL PLATED	NL2-3u	1

UNLESS OTHERWISE SPECIFIED TOLERANCE	
ANG.	±5°
D.	±
.0	±0.25
.00	±0.20



SCALE: AS SHOWN	UNIT: mm
DRAWN: willis	2007/4/23
CHECKED: / /	
APPROVED: / /	
SIZE: A4	REV.:

DRAWN NAME: USB Type B type
4Pin SMT
PRODUCT NO. USB-B-HR-S
FILE NAME: USB-B-HR-S

REV.	DESCRIPTION	DATE