



(COMPONENT SIDE)
PCB LAYOUT

USB - B - V V - D - 1 - 2 - 3

Part Number

1. Contact Plating
N: *Nickel Plating
B: Gold Flash
C: 30u" Gold Plating
2. Shell Plating
N: *Nickel Plating
G: Gold Plated
3. Insulator Color
_: *White
B: Black * standard

NO.	NAME	MATERIAL	FINISH	REMARK	Q'TY
1	HOUSING	P.B.T. G.F.	WHITE		1
2	PIN TERM.	PHOS. BRONZE T:0.25	GOLD/TIN PLATED	Gold:1~3u" ; Ni:60~80u" ; TIN:120u" (100% pure Tin of lead free plating)	4
3	SHELL	BRASS T:0.3	NICKEL PLATED	Ni:80~120u"	1
4	BOTTOM COVER	P.B.T. G.F.	WHITE		1

UNLESS OTHERWISE SPECIFIED TOLERANCE	
ANG.	±5°
0.	±
.0	±0.25
.00	±0.20



SCALE: AS SHOWN	UNIT: mm
DRAWN: willis	2007/3/27
CHECKED: / /	
APPROVED: / /	

DRAWN NAME: USB-B Type
Dip Type, Straight 180°
PRODUCT NO. USB-B-V V-D
FILE NAME: USB-B-V V-D

REV.	DESCRIPTION	DATE	SIZE	REV.
			A4	