

Note:

1.Material:

- 1.1 Insulator: NY6T UL 94-V0 rated.
- 1.2 Contact: Brass,t=0.25mm.
- 1.3 Shell: Cold rolled steel,t=0.30mm.

2.specification:

- 2.1 Current rating:1A MAX.
- 2.2 Dielectric withstanding voltage:500 v(ac) far minuta.
- 2.3 Contact resistance: 30 m Ω max.
- 2.4 Insulation resistance: 1000 M Ω min at DC 500V.
- 2.5 Total mating force: 3.57 kgf max.
- 2.6 Total unmating force: 0.71 kgf min.
- 2.7 Temperature range: -55°C~+105°C.

| | | | | | |
|-----|-----------|------|-------------------|---------------|---------------|
| 3 | SHELL | 1 | Cold rolled steel | T=0.30±0.02mm | Nickel Plated |
| 2 | CONTACT | 5 | Brass | T=0.25±0.02mm | gold plating |
| 1 | HOUSING | 1 | NY6T | | Black |
| No. | Part Name | Q'ty | Material | Thickness | Finish |

UNLESS OTHERWISE SPECIFIED TOLERANCE

ANG. ±5
0. ±0.3
.0 ±0.25
.00 ±0.20

SCALE: AS SHOWN UNIT: mm

DRAWN Willis 2008/6/24

CHECKED / /

APPROVED / /

DATE SIZE A4 REV.



DRAWN NAME: Mini USB 5 pin B Connector DIP Type


PRODUCT NO. USB-M-E-MXN0-R01

FILE NAME:

REV.

DESCRIPTION

DATE



SIZE A4

REV.