



RoHS  
Compliance

5	CONTACT	CuBe	1	Ag PLATED					
3	TERMINAL	BRASS	6	Ag PLATED	4	COVER BOARD	S U S	1	
1	FRAME	NYLON 46	1		2	KNOB	NYLON 46	1 CGA 1-2	
NO.	PART	MATERIAL	QTY	REMARKS	NO.	PART	MATERIAL	QTY	REMARKS

<b>ISSUED</b>	<b>SPECIFICATION</b>	<b>TITLE:</b> MINIATURE SIDE KNOB SLIDE SWITCH (1P4T)		
	RATING: DC 12V 0.1A	<b>MODEL NO:</b> MSK-14C01		
	CONTACT RESISTANCE: 70mΩ max.			
	INSULATION RESISTANCE: 100MΩ AT 500V DC	TOLERANCE	UNIT: MM	DWN.
	WITHSTAND VOLTAGE: AC 100V for 1 minute	UP TO 1.0:±0.1	SCALE: 5:1	CHK'D.
	OPERATION FORCE: REFER ATTACH SPECIFICATION	1.0 TO 10.0:±0.2	VERSION: 02	APPD.
	SWITCHING LIFE: 10K cycles min.	OVER 10.0:±0.3	DRWG NO:	

BY:   
DATE: 07-AUG-2007

