


SCHEMATIC



P.C.B. LAYOUT

RoHS Compliance

5	CONTACT	P B S	1	Ag PLATED					
3	TERMINAL	BRASS	3	Ag PLATED	4	COVER BOARD	S U S	1	
1	FRAME	NYLON 46	1		2	KNOB	NYLON 46	1	
NO.	PART	MATERIAL	QTY	REMARKS	NO.	PART	MATERIAL	QTY	REMARKS

ISSUED	SPECIFICATION	TITLE: MINIATURE SLIDE SWITCH (1P2T)		
	RATING: DC 12V 0.1A	MODEL NO: MSS-12D19		
	CONTACT RESISTANCE: 70mΩ max.	TOLERANCE	UNIT: MM	DWN.
	INSULATION RESISTANCE: 100MΩ AT 500V DC	UP TO 1.0:±0.1	SCALE: 5:1	CHK'D.
	WITHSTAND VOLTAGE: AC 100V for 1 minute	1.0 TO 10.0:±0.2	VERSION: 03	APPD.
	OPERATION FORCE: REFER ATTACH SPECIFICATION	OVER 10.0:±0.3	DRWG NO:	
	SWITCHING LIFE: 10K cycles min.			

BY:   
DATE: 07-AUG-2007

