





RoHS  
Compliance



SCHEMATIC



PCB LAYOUT



5	CONTACT	S U S	1	Ag PLATED					
3	TERMINAL	BRASS	4	Ag PLATED	4	COVER	S U S	1	
1	FRAME	NYLON 46	1	BLACK	2	KNOB	NYLON 46	1	BLACK
NO	PART	MATERIAL	QTY	REMARKS	NO	PART	MATERIAL	QTY	REMARKS

ISSUED

SPECIFICATION

TITLE: TACT SWITCH

RATING: DC 12V 50mA

CONTACT RESISTANCE: 100mΩ Max.

INSULATION RESISTANCE: 100MΩ at 500V DC

WITHSTAND VOLTAGE: AC 250V for 1 minute.

OPERATION FORCE: REFER ATTACH SPECIFICATION

SWITCHING LIFE: 100k Cycles Min.

MODEL NO: TC-12020A-00-D-N

TOLERANCE UNIT: MM

UP TO 1.0:±0.1 SCALE: 5:1

1.0 TO 10.0:±0.2 VERSION: 02


OVER 10.0:±0.3 DRWG NO:

DWN. *Jm*  
CHK'D. *Jm*  
APPD. *Lizy*

BY: *Lizy*

DATE: 28-Jun-2012



**VIMEX**  
INTERNATIONAL CORPORATION





RoHS  
Compliance



SCHEMATIC



PCB LAYOUT



5	CONTACT	S U S	1	Ag PLATED					
3	TERMINAL	BRASS	4	Ag PLATED	4	COVER	S U S	1	
1	FRAME	NYLON 46	1	BLACK	2	KNOB	NYLON 46	1	BLACK
NO	PART	MATERIAL	QTY	REMARKS	NO	PART	MATERIAL	QTY	REMARKS

ISSUED	SPECIFICATION				TITLE: TACT SWITCH					
	RATING: DC 12V 50mA				MODEL NO: TC-12020A-00-D-E					
	CONTACT RESISTANCE: 100mΩ Max.									
	INSULATION RESISTANCE: 100MΩ at 500V DC				TOLERANCE	UNIT: MM	DWN.	Jm		
	WITHSTAND VOLTAGE: AC 250V for 1 minute.				UP TO 1.0:±0.1	SCALE: 5:1	CHK'D.	mm		
	OPERATION FORCE: REFER ATTACH SPECIFICATION				1.0 TO 10.0:±0.2	VERSION: 02	APPD.	Lizy		
	SWITCHING LIFE: 100k Cycles Min.				OVER 10.0:±0.3	DRWG NO:				

BY: *Lizy*  
DATE: 28-Jun-2012

